

NSV102A

Spindle Speed	12,000 (15,000)
Spindle Taper	BBT 40
X / Y / Z Axis Travel	1020 / 600 / 600 mm
Table Size	1120 mm x 650 mm
Max. Load on Table	1000 kg
Tool Magazine Capacity	30 (48) T
Machine Weight	7000 kg



Spindle		
Spindle Speed	12,000 (15,000)	rpm
Spindle Power	7.5/11/15/18.5/22	kw
Spindle Taper	BBT40	
Travel		
X Axis Travel	1020	mm
Y Axis Travel	600	mm
Z Axis Travel	600	mm
Distance Between Spindle Nose & Table Top	100~700	mm
Table		
Table size	1120×650	mm
T-Slots×Size×Pitch	6×18 mm×100	mm
Max. Load on Table	1,000	kg
Feed		
Rapid Feed Rate	48	m/min
Cutting Feed Rate	1~20,000	mm/min
Accuracy ISO (Linear)		
Positioning	0.010	mm
Repeatability	0.007	mm
Accuracy JIS B (300mm)		
Positioning	0.003	mm
Repeatability	±0.002	mm
ATC		
Tool Magazine Capacity	30T [48T]	
Max. Tool Weight (per piece)	6	kg
Max. Tool Dimensions	ø76 ×300	mm
Tool Change Time	2.5 sec. (T-T)	
Tool Changer Method	Arm Type	
Tool Selection Method	Random	
General		
Pneumatic Supplier	5.5	kg/cm ²
Power Consumption	33	kva
Machine Weight	7,000	kg